

DUALIFT Standard Features:

- ✓ Collapsible rear under-ride
- ✓ Poly fenders
- ✓ Steel side mount hydraulic oil tank
- ✓ Safety Props
- ✓ Mid-turn signal
- ✓ Back-up & hoist-up alarms
- ✓ Side rollers (5/side) 4" OD x 3-1/2" L greaseable bronze bushings with outboard support
- ✓ Design allows single tire pusher axle
- ✓ Outside valve control
- ✓ Shut off valve 2", 1/4 turn full-flow
- ✓ Rear container hold-down strap
- ✓ Enclosed 8-1/4" rear roller greaseable



DUALIFT is a better hook lift:

- Lower loading height and lift angle.
- Services container lengths 12'-24'
- Services lift bar heights 36", 54" & 62"
- Cable type frame rail stability
- Compliant rear under-ride.



Model	HC6022	HC6024
Capacity - cable	60,000 lbs.	60,000 lbs.
- hook	65,000 lbs.	65,000 lbs.
Container lengths	12' to 22'	12' to 24'
Cab to Tandem	184"	204"
Hook Height	36", 54" and 62"	
Cylinders:		
lift, carriage, hook	6", 7", 4"	
Hydraulic pump	50 gpm	
Filter	High pressure full flow	
Operating pressure	2500 psi max	
Dump angle	50°	
Frame	9" channel 2"x4" sub-frame	
Rear Hinge	2-1/2"	
Sheave (one)	14"	
Cable length (7/8")	28 feet	30 feet
Cable anchor end	Terminator wedge	

DUALIFT is a better cable hoist:

- Twice the alignment forgiveness of reeving hoists
- Faster than reeving operations
- Breaks stubborn loads free
- Powers short containers to rear of frame before raising
- 10' cable at rear of hoist, excellent for tough pulls



DUALIFT loads pup trailers:

- Easy and fast loading.
- Controlled movement of hook *and* cable containers onto pup trailer.
- Safer method to load pup trailers.

DUALIFT Available Options:

- ✓ Pintle Hook frame assembly
- ✓ Pintle Hook
- ✓ LED lights
- ✓ Automatic tarper
- ✓ Tarper ready hydraulics
- ✓ Wet-line kit
- ✓ Fire extinguisher rack
- ✓ Air shift PTO
- ✓ Inside air controls
- ✓ Tool box
- ✓ Steel or Aluminum fenders
- ✓ Hook style rear container hold-down
- ✓ 54" high mast (54" & 36" lift bars)

Refuse Parts, LLC

PO Box 237, 3424 State Route 309

Iberia, OH 43325-0237

Phone: (419) 468-5095 Fax: (419) 462-1200

Email: info@refuseparts.com

Website: www.refuseparts.com

Distributed by: